

METHOD AND DEVICE FOR DAMPING CONTROL OF OSCILLATING
MODES OF A CONTINUOUSLY VARIABLE TRANSMISSION PROVIDED
WITH AN ELECTRIC VARIATOR

5 The present invention relates to the control of infinitely variable transmissions with electric variator.

10 More precisely, its subject is a method of damping the oscillating modes of an infinitely variable transmission with electric variator, comprising a heat engine and at least two electric machines, as well as a supervising device, affording regulation of the torque at the wheels and of the status of the heat engine.

15 This invention applies to a vehicle equipped with a heat engine and with an infinitely variable transmission with electric variator, which exhibits the particular feature of not comprising any coupler, clutch or converter, between the heat engine and the transmission.

25 It finds a favored, but nonlimiting application on a transmission device of the type comprising at least two parallel paths for power transmission, one path containing a kinematic chain with fixed gearing, and another path containing a continuous speed variator, composed of two electric machines.

30 The publication FR 2 823 281 discloses a device of the type indicated above, according to which the various paths are connected on the one hand to an input mechanical distributor linked to a mechanical energy source such as a heat engine, and on the other hand to
35 an output mechanical distributor linked to the wheels of the vehicle. The input and output mechanical distributors, are preferably, but not necessarily, epicyclic gear trains.

The transmission described in this publication thus comprises two electric machines linked by an energy buffer element, which are integrated into a kinematic chain having four input and output shafts, respectively connected to the heat engine, to the wheels, and to the electric motors.

According to a customary arrangement within the field, a transmission calculation unit establishes instruction setpoints for each actuator (the two electric machines, and possibly the heat engine), making it possible to place the transmission on an operating point determined by other calculation modules called "higher monitoring layers", in the following four basic situations:

- "torque tracking", where the driver presses the accelerator: the target of the computer is a wheel torque and a status of the heat engine required by the monitor (this is the commonest case where the heat engine provides an engine torque),
- "fuel cutoff", where the driver does not press the accelerator, and where injection is cut off to the heat engine and the latter provides a resistive torque; the target is a thermal status required by the monitor,
- "speed creeping", where the vehicle moves at low speed, the driver pressing neither the accelerator nor the brake; the target is a thermal status required by the monitor, and
- "torque creeping", where the vehicle moves at low speed, the driver pressing the brake pedal.

35

The calculation unit in charge of establishing the instruction setpoints of each actuator must in particular comply with the performance specifications,

and must resist various disturbances, or "control noise" of the system, whilst affording regulation of the energy buffer element.

- 5 Among these disturbances are the oscillations caused by all the stiffnesses lying between the engine and the wheels. The better the performances, the more sensitive to these stiffnesses are the compliance and robustness of the regulating of the engine power plant.

10

Ignoring them restricts the performance of the regulating device, since excessive performance degrades the robustness, brings about oscillations, and leads to the instability of the regulating device.

15

The aim of the present invention is to remove the oscillating effect of these stiffnesses, especially in the four situations indicated above, on the basis:

- 20 - of the tracking of a wheel torque reference,
- of the tracking of a heat engine status reference,
and
- of a damping of the oscillations brought about by the stiffnesses of the mechanical links (damping
25 flywheel, differential, shafts, etc) between the heat engine, the transmission and the wheels.

With this aim, it proposes that the torque instruction of the electric machines be the sum of a main
30 instruction making it possible to attain setpoints for wheel torque and torque of the heat engine, and of an instruction supplement intended to damp the oscillating modes brought about by the stiffnesses of the kinematic chain between the heat engine and the wheels.

35

In accordance with the invention, the instruction supplement depends on the setpoint signals and on estimates of physical quantities.

According to another characteristic of the invention, this instruction supplement is calculated by a unit for damping the oscillating modes.

5

It is added to an instruction setpoint for the electric machines, established by a unit for mechanical decoupling between the heat engine and the electric machines.

10

According to a preferred embodiment of the invention, the supervising device implemented comprises a mechanical supervising unit affording regulation of the torque at the wheels and status of the heat engine, which groups together a mechanical determination unit, a mechanical regulating unit, a mechanical decoupling unit, and a unit for damping the torsional modes.

15

Other characteristics and advantages of the present invention will become clearly apparent on reading the following description of a nonlimiting embodiment thereof, referring to the appended drawings, in which:

20

- figure 1 is an infinitely variable transmission type diagram to which the invention applies,
- figure 2 depicts on this diagram the stiffnesses modeling taken into account,
- figure 3 shows the structure of the mechanical supervision implemented according to the invention, and
- figure 4 is a diagram of the unit for damping the torsional modes.

25

30

Represented diagrammatically in figure 1 is an infinitely variable transmission with electric variator exhibiting two parallel paths for power transmission between the heat engine 1 and the wheels 6, such as is described in publication FR 2 823 281 to which reference may be made. The main power path comprises a

35

kinematic chain with fixed gearing, and the so-called power bypass path includes the two electric machines 2, 3 constituting the variator. In the diagram, the physical quantities explained below have been
5 mentioned: T_{ice} , T_i , W_{ice} , T_{e1} , T_{e2} , W_{e1} , W_{e2} , T_o , W_{wh} , and T_{res} .

The physical quantities characterizing the overall behavior of the EPP equipped with its infinitely
10 variable transmission with electric variator that are mentioned in the diagrams are as follows.

At the level of the heat engine;

- T_{ice} : engine torque applied to the crankshaft,
- 15 - W_{ice} : engine status

At the level of the damping flywheel:

- T_i : torque exchanged between the heat engine and the box,
- W_i : status at the output of the flywheel,

20 At the level of the power bypass:

- T_{e1} : torque of the first electric machine 2
- W_{e1} : status of the first electric machine 2
- T_{e2} : torque of the second electric machine 3
- W_{e2} : status of the second electric machine 3
- 25 - U_{capa} : voltage across the terminals of the energy storage element:

At the level of the differential:

- W_o : status at the output of the kinematic chain
- T_o : wheel torque

30 At the level of the wheel:

- W_{wh} : speed of the wheels
- T_{res} : resistive torque

As indicated in a nonlimiting manner in figure 2, the main stiffnesses of the engine power plant of figure 1
35 are assumed to be grouped together at the output of the heat engine and on the wheels. Specifically, these two stiffnesses appear explicitly in the model of the dynamic behavior of this engine power plant.

The transmission possibly being in one of the four situations cited (torque tracking, fuel cutoff, speed creeping, and torque creeping), the transmission
5 supervising device comprises a mechanical supervising unit adapted to these four situations. More precisely, it must meet, in each of them, the mechanical objectives of the supervision, namely the regulating of the wheel torque T_o , and of the status of the heat
10 engine W_{ice} .

The energy objective is moreover afforded by an energy supervising unit (not described), only the outgoing signals of which interacting with the mechanical
15 supervision are mentioned:

- U_w : energy instruction which is expressed as a function of T_{e1} , T_{e2} , W_{e1} and W_{e2} ,
- $E_{T_{e1}}$: estimate of the torque of the first electric
20 machine,
- $E_{T_{e2}}$: estimate of the torque of the second electric machine,

The mechanical supervising unit is itself composed of
25 four units or modules grouped together in figure 3, with the various signals which are associated with them: a mechanical determination unit 9, a mechanical regulating unit 8, a mechanical decoupling unit 7, and a unit for damping the torsional modes 4.

30

The mechanical determination unit 9 has the function of providing the state of the system to the other mechanical supervising units. For this purpose, it utilizes the measurements of status W_{e1} , W_{e2} of the
35 electric machines 2, 3, as well as the energy instruction U_w , which is expressed as a function of the respective torques $E_{T_{e1}}$, $E_{T_{e2}}$, of these machines. The unit 9 also utilizes a signal $R_{T_{ice}}$, emanating from the

mechanical decoupling unit and which represents the engine torque setpoint sent to the computer of the heat engine.

5 On the basis of these measurements and signals, the mechanical determination unit calculates the following quantities:

- EWice: estimate of the engine status,
- 10 • ETo: estimate of the wheel torque,
- EWel and EWe2: estimates of the statuses of the electric machines, and
- an estimation vector Xf, which comprises the above estimates, as well as ETi estimate of the torque Ti
- 15 exchanged between the engine and the box, an estimate of the speed at the wheels EWwh, an estimate of the heat engine frictional torque Etdice, and an estimate of the frictional torque at the wheel ETres.

20 The vector Xf is therefore of the form:
$$Xf = [EWice, EWwh, EWel, EWe2, ETi, ETo, Etdice, ETres]$$

This vector contains an estimate of the state of the transmission as a whole, in interaction with the heat
25 engine and the wheels. This estimate is destined for the other units of the mechanical supervision. The calculation of these estimates as a whole is made possible by virtue of the known techniques for observing and estimating dynamic systems, and is based
30 on a standard mathematical model of the dynamic behavior of the engine power plant.

The mechanical regulating unit calculates two intermediate control signals v1 and v2, on the basis of
35 the engine status reference RWice, wheel torque reference RTo, engine status estimate EWice and wheel torque estimate (ETo):

- 8 -

- the signal $v1$ is calculated by a regulator on the basis of the thermal status setpoint R_{Wice} and of the estimate of the thermal status E_{Wice}

- the signal $v2$ is also calculated by a regulator on the basis of the wheel torque setpoint R_{To} and of the estimate of the wheel torque E_{To} .

The parameters of these two regulators are adjustment parameters for the mechanical regulating unit, which determine the degree of performance of the tracking of the setpoints R_{Wice} and R_{To} by the quantities $Wice$ and To .

The mechanical decoupling unit 7 calculates an instruction $Uo1$ and a setpoint R_{Tice} for the heat engine torque on the basis of the intermediate instructions $v1$ and $v2$ of the estimation vector Xf emanating from the mechanical determination unit. This instruction ensures the tracking of the setpoints R_{Wice} and R_{To} , but cannot by itself deal with the damping of the oscillations brought about by the mechanical stiffnesses.

Finally, the unit for damping the torsional modes 4 (UAM), which calculates an instruction supplement Um which is added to $Uo1$: Um depends on the signals R_{Wice} , R_{To} and on the vector Xf . The instruction $Uo1$ is converted into electrical control torques $Te1$ and $Te2$.

As indicated above, one of the essential characteristics of the solution proposed relates to the unit for damping the torsional modes (UAM). This unit provides an instruction supplement Um , damping the oscillating modes brought about by the stiffnesses. This instruction gets added to the instruction $Uo1$ calculated by the mechanical decoupling unit, to obtain the final instruction Uo .

In accordance with the invention, the signal U_m is the result of a linear combination of the elements of X_f , namely of estimates of physical quantities, and setpoint signals R_{Wice} and R_{To} .

5

Figure 4 explains this calculation, and brings in various weighting parameters a_i and b_j . As indicated in this figure, the instruction U_m has two components, U_{mc} and U_{me} , such that $U_m = U_{mc} + U_{me}$:

10

- U_{mc} is a linear combination of the setpoints R_{Wice} and R_{To} :

$U_{mc} = a_1 R_{Wice} + a_2 R_{To}$, and

- U_{me} is a linear combination of the components of the vector X_f :

$U_{me} = b_1 E_{Wice} + b_2 E_{Wwh} + b_3 E_{We1} + b_4 E_{We2} + b_5 E_{Ti} + b_6 E_{To} + b_7 E_{Tdice} + b_8 E_{Tres}$.

The coefficients a_i and b_j are mapped as a function of the operating point of the vehicle. Their value can be calculated on the basis of various algorithms well known in the state of the art in automation (pole placement, energy optimization, robust control, etc.). They also constitute fine-tuning parameters for calibrating the unit for damping the oscillating modes.

The invention has numerous advantages. In each of the situations on the move: torque tracking, fuel cutoff, speed creeping and torque creeping, the solution proposed has the advantage of dealing with the oscillations brought about by the various mechanical stiffnesses. The instruction delivered by the unit for damping the torsional modes, U_m gets added to the instruction U_{o1} to give a final instruction U_o which makes it possible to act on the electric actuators to damp the oscillations.

Failure to deal with the stiffnesses leads in fact to mediocre benefit in the vehicle, as the mechanical regulating must ensure high performance in terms of the tracking of engine status setpoint, and of wheel
5 torque.

The calculation of U_m performed in the unit of damping the torsional modes, has the advantage finally of relating to estimates of physical quantities, this
10 being of importance for fine-tuning.